

IP Camera		
Model	IPH-1SP-IR	
Version	-	
Image Sensor		
Sensor	1/4" OmniVision	
Pixel Size, $\mu\text{m}$	3.0x3.0	
Resolution, points@fps	Main stream	PAL:1280x720@25, 704x576@25, NTSC:1280x720@30, 704x576@30
	Sub stream	PAL:704x576@25, 320x288@25, NTSC:704x576@30, 320x288@30
Day/Night mode	Auto/Color/Black&White	
Sensitivity, Lux/Iris	Color 0.6Lux@F1.2, Black/White: 0.08 Lux@F1.2	
Dynamic range WDR, dB	69	
S/N ratio, dB	39	
Video functions	AEC, AGS, AWB, ABF, ABLC, OSD, PrivacyMasks	
Codec profile	H.264	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-5120
	Variable	Worst/Worse/General/Good/Better/Best
Lens		
Focal length, mm	3.6	
Iris, F	1.2	
Angle of View, $^{\circ}$	Horizontal	59
	Vertical	40
lens Type	Aspherical	-
	Spherical	+
Lens mount	M12	
Control	Pan, $^{\circ}$	355
	Tilt, $^{\circ}$	120
IR LED		
Distance, m	Up to 15	
Number of LEDs, pcs.	11	
Beam Spread, $^{\circ}$	60	
Wavelength, nm	850	
IR Cut Filter	Auto	
Network		
Network Interface	RJ-45 (10/100Base-T)	
Wireless LAN(WiFi)	+	
Network functions	Cloud/NIP/DDNS/IPFilter/E-mail/NTP/PPPoE/UPNP/FTP/RTSP	
Browser supported	Internet Explorer, Opera, Mozilla Firefox, Google Chrome	
Languages supported	English, Russian, Arabic, French, Poland, Romanian, Hungarian, Italian	
Default IP address	<b>192.168.1.10</b>	
Username	<b>Admin</b>	
Password	<b>Empty by default</b>	
HTTP port	80	
ONVIF port	8899	
RTSP port	554	
RTSP string	rtsp://192.168.1.10:554 /user=admin&password=&channel =1&stream=0.sdp?	
Control port	34567	
Software supported	Free	Partizan Device Maneger
	iOS	Partizan Cloud, Partizan Device Maneger
Mobile software	Android	Partizan Cloud, Partizan Device Maneger
	System Integration	Partizan SDK, ONVIF 2.4+
Dimensions		
Size, mm	Total length	148
	Housing	$\varnothing$ 128x148
	Bracket	-
Weight, g	360	
Common		
Power Supply	DC,V/A	5/1
	PoE, Class/W	-
Alarm	Inputs	+
	Outputs	-
Audio	+	
Memory card	MicroSD(Up to 32Gb)	
Housing material	Plastic	
Bracket material	-	
IP rating	44	
IK rating	-	
Operating temperature, $^{\circ}\text{C}$	+10 - +55	
Warranty, years	3	